

PROTECTOR DE LINHA PREFORMADO**PROTECTOR DE LÍNEA PREFORMADO****LINE GUARDS****Uso e Aplicação**


Material indicado para ser usado como proteção mecânica dos cabos de alumínio nos pontos de derivação, pontos de suspensão em linhas leves e pontos de amarração nos isoladores quando não se usa o Laço Preformado.

Uso y Aplicación

Material indicado para ser usado como protección mecánica de los cables de aluminio en los puntos de derivación, puntos de suspensión livianos y puntos de amarre cuando no se usa la Amarra Fija Central.

General Recommendations

Material designed to protect against abrasion and arc-over, and to provide limited repair, are also recommended as minimum protection for hand-tie spans. The Line Guards also may be used as tap armor to protect conductors from wear and flash-over damage under hot line taps.



CATAL. cód./cód. number	Intervalo Aplic (mm) Rango Aplic. (mm)		Diameter Range (in)		Cabo/Cable/Conductor Size(awg/mcm)				Comp/Largo Lenght		Varetas p/ Conj Varillas p/ Conj	Cód. Cor Color
	min	max	min	max	CAA ACSR	CA AAC	CAL AAAC	Compactado Compacted	(mm)	(inches)	Rods per Set	Color Color Code
ILG-9122 ILG-9305	4,62	4,91	.182	.193	—	6 - 7f/h/w	—	—	432	17(S) 737 29(D)	7	púrpura/rosa/purple
ILG-9123 ILG-9306	4,92	5,26	.194	.207	6 - 6/1	—	6 - 7f/h/w	—	432	17(S) 737 29(D)	7	azul/azul/blue
ILG-9125 ILG-9308	5,59	5,79	.220	.228	5 - 6/1	—	5 - 7f/h/w	—	432	17(S) 737 29(D)	7	branco/blanco/white
ILG-9126 ILG-9309	5,81	6,18	.229	.243	—	4 - 7f/h/w	—	4 - 6/1,7/1f/h/w	483	19(S) 787 31(D)	8	marrom/marron/brown
ILG-9127 ILG-9310	6,19	6,59	.244	.259	4 - 6/1,7/1	—	4 - 7 f/h/w	—	483	19(S) 787 31(D)	8	laranja/naranja/orange
ILG-9128 ILG-9311	6,60	6,93	.260	.273	—	3 - 7f/h/w	—	2 - 7f/h/w	483	19(S) 787 31(D)	8	verde/verde/green
ILG-9129 ILG-9312	6,94	7,34	.274	.289	—	—	3 - 7 f/h/w	—	533	21(S) 838 33(D)	9	amarelo/amarillo/yellow
ILG-9130 ILG-9313	7,35	7,82	.290	.308	—	2 - 7f/h/w	—	—	533	21(S) 838 33(D)	9	púrpura/rosa/purple
ILG-9131 ILG-9314	7,83	8,28	.309	.326	2 - 6/1,7/1	—	2 - 7 f/h/w	—	533	21(S) 838 33(D)	9	vermelho/rojo/red
ILG-9132 ILG-9315	8,29	8,79	.327	.346	—	1 - 7f/h/w	—	1/0 - 7,19f/h/w	533	21(S) 838 33(D)	10	azul/azul/blue
ILG-9133 ILG-9316	8,80	9,31	.347	.366	1 - 6/1	—	—	1/0 - 6/1	584	23(S) 889 35(D)	10	verde/verde/green
ILG-9134 ILG-9317	9,32	9,89	.367	.389	—	1/0 - 7f/h/w	—	2/0 - 7,19 f/h/w	584	23(S) 889 35(D)	11	preto/negro/black
ILG-9135 ILG-9318	9,90	10,49	.390	.413	1/0 - 6/1	—	1/0 - 7 f/h/w	—	635	25(S) 940 37(D)	11	amarelo/amarillo/yellow

Encordoamento à direita

Encordonamiento a la derecha

Right-hand lay standard

(S) Comp p/ Aplic 1 Isol./Largo para Aplic 1 Aisl.

(D) Comp p/ Aplic Isol. Duplo/Largo para Aplic doble Aisl.

(S) Single Support Length

(D) Double Support Length