

**ALÇA PREFORMADA DE SERVIÇO**

**REMATE PREFORMADO PARA ACOMETIDA**

**SERVICE DEAD END**

**Uso e Aplicação**

Material indicado para ser usado em cabos mensageiros (neutro) de cabos auto sustentáveis (multiplex), e também em cabos de alumínio simples de ramais de serviço com vãos não maiores que 45 metros.

**Uso y Aplicación**

Material indicado para ser usado en cables mensajeros (neutro) de cables autoportables (multiplexados), y también en cables de aluminio sencillos para acometidas en vanos no más grandes que 45 metros.

**General Recommendations**

Material designed for bare neutral messengers of self-supporting cable used in making service drops not exceeding 45 meters (150 feet)



CATAL. código	Intervalo de Aplic. Rango Aplicación		Diameter Range		Cabo/Cable/Conductor Size				Comprim (max) Largo (max)		Cód. Cor Color
	min	max	min	max	CAA	CA	CAL	Multiplex Neutro	Lenght (max)	Color Code	
number	(mm)	(inches)			ACSR	AAC	AAAC	mm2	(mm)(inches)		
SDE-9900	3,70	4,02	.145	.158	8 - 6/1	—	—	10-CA/CAA/CAL	292 11,5	marrom/marron/brown	
SDE-9500	4,29	5,04	.169	.198	6 - 6/1	6 - 7f/h/w	6 - 7f/h/w	—	279 11	azul/azul/blue	
SDE-9501	5,05	5,70	.199	.224	5 - 6/1	4 - sol.	5 - 7f/h/w	16-CA/CAA/CAL	305 12	branco/blanco/white	
SDE-9502	5,71	6,54	.225	.257	4 - 6/1 4 - 7/1	4 - 7f/h/w	4 - 7f/h/w	25-CA/CAA/CAL	330 13	laranja/naranja/orange	
SDE-9503	6,55	7,35	.258	.289	3 - 6/1	3-7f/h/w—2 - sol.	3 - 7f/h/w	—	356 14	preto/negro/black	
SDE-9504	7,36	8,27	.290	.325	2 - 6/1—2 - 7/1	2 - 7f/h/w	2 - 7f/h/w	35-CA/CAA/CAL	381 15	vermelho/rojo/red	
SDE-9505	8,28	9,15	.326	.360	1 - 6/1	1 - 7f/h/w	1 - 7f/h/w	50-CA/CAL	432 17	verde/verde/green	
SDE-9506	9,16	10,17	.361	.400	1/0 - 6/1	1/0 - 7f/h/w	1/0 - 7f/h/w	50-CAA	483 19	amarelo/amarillo/yellow	
SDE-9507	10,18	11,44	.401	.450	2/0 - 6/1	2/0 - 7f/h/w	2/0 - 7f/h/w	70-CA/CAA/CAL	533 21	azul/azul/blue	
SDE-9508	11,45	12,96	.451	.510	3/0 - 6/1	3/0 - 7f/h/w	3/0 - 7f/h/w	95-CA/CAA/CAL	584 23	laranja/naranja/orange	
SDE-9509	12,97	14,74	.511	.580	4/0-6/1—4/0-18/1	4/0 - 7f/h/w	4/0 - 7f/h/w	120-CA/CAL	660 26	vermelho/rojo/red	

Encordoamento à direita

Encordonamiento a la derecha

Right-hand lay standard