

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/ mcm)		Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ACSR)	(mm)	(inches)	
DDE/OR-9541	5,81	6,52	0.229	0.257	4 - 7f/h/w	4 - 6/1, 7/1	350	14	laranja, naranja, orange
DDE/OR-9542	7,36	8,25	0.290	0.325	2 - 7f/h/w	2 - 6/1, 7/1	430	17	vermelho, rojo, red
DDE/OR-9544	9,27	10,40	0.365	0.409	1/0 - 7f/h/w	1/0 - 6/1	510	20	amarelo, amarillo, yellow
DDE/OR-9545	10,41	11,69	0.410	0.460	2/0 - 7f/h/w	2/0 - 6/1	560	22	azul, azul, blue
DDE/OR-9547	13,13	14,67	0.517	0.577	4/0 - 7f/h/w	4/0 - 6/1	775	31	vermelho, rojo, red
DDE/OR-9549	16,61	17,69	0.654	0.696	336.4 - 19f/h/w	300 - 26/7 336.4 - 18/1	980	39	verde, verde, green
DDE/OR-9581	17,70	18,78	0.697	0.739	397.5 - 19f/h/w	336.4 - 26/7	990	39	amarelo, amarillo, yellow