

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size - awg	Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Cod. Color del Conductor Conductor Color Code
	min	max	min	max		(mm)	(inches)	
DDE/J-8510	5,82	6,53	0.229	0.257	6 - 7f/h/w, 2/64s 6-solid, 3/64s	457	18	laranja, naranja, orange
DDE/J-8511	6,54	7,34	0.258	0.289	4-solid, 2/64s 6 - 7f/h/w, 3/64s	533	21	amarelo, amarillo, yellow
DDE/J-8512	7,35	8,25	0.290	0.325	6 - 7f/h/w, 4/64s 4 - 7f/h/w, 2/64s	660	26	vermelho, rojo, red
DDE/J-8513	8,26	9,24	0.326	0.364	4 - 7f/h/w, 3/64s 4 - 7f/h/w, 4/64s	686	27	verde, verde, green
DDE/J-8514	9,25	10,39	0.365	0.409	2 - 7f/h/w, 3/64s 4 - 7f/h/w, 5/64s	686	27	amarelo, amarillo, yellow
DDE/J-8515	10,40	11,68	0.410	0.460	2 - 7f/h/w, 5/64s 4 - 7f/h/w, 4/64s	737	29	azul, azul, blue
DDE/J-8516	11,69	13,10	0.461	0.516	1-19f/h/w, 5/64s 1/0 - 7f/h/w, 4/64s	787	31	laranja, naranja, orange
DDE/J-8517	13,11	14,65	0.517	0.577	1/0 - 19f/h/w, 5/64s 1/0 - 19f/h/w, 6/64s	864	34	púrpura, rosa, pink
DDE/J-8100	14,66	16,58	0.578	0.653	3/0 - 7f/h/w, 4/64s 4/0 - 7f/h/w, 4/64s	889	35	azul, azul, blue
DDE/J-8101	16,59	18,77	0.654	0.739	250 - 19f/h/w, 4/64s 266.8 - 19f/h/w, 4/64s	965	38	vermelho, rojo, red
DDE/J-8102	18,78	21,26	0.740	0.837	300 - 19f/h/w, 5/64s 336.4 - 19f/h/w, 8/64s	1016	40	marrom, marron, brown
DDE/J-8103	21,27	24,05	0.838	0.947	336.4 - 19f/h/w, 8/64s 397.5 - 19f/h/w, 6/64s	1016	40	verde, verde, green
DDE/J-8104	24,06	27,20	0.948	1.071	477 - 37f/h/w, 5/64s 500 - 37f/h/w, 8/64s	1016	40	preto, negro, black
DDE/J-8105	27,21	30,78	1.072	1.212	350 - 19f/h/w, 12/64s 500 - 37f/h/w, 12/64s	1016	40	púrpura, rosa, pink